


PROJECT VRF R410A FULL DC INVERTER

.....

HTFU XRV-P Compact cassette 60x60



The control must be purchased as an accessory



Ultra-compact design

22 dB(A) (2.20~2.80 kW) | Extremely quiet

360° air diffusion

Condensate drain pump with possibility of raising the discharge up to 500 mm from the lower height

Model		HTFU 225 XRV-P	HTFU 285 XRV-P	HTFU 365 XRV-P	HTFU 455 XRV-P
Control (included)	type	none			
Rated cooling capacity	kW	2.20	2.80	3.60	4.50
Rated heating capacity	kW	2.40	3.20	4.00	5.00
Electrical data					
Power supply	Ph-V-Hz	1-220~240V-50Hz			
Electrical absorption	W	35	35	40	50
Product specifications					
Air flow (1)	Max~Min	m³/h 576~405		604~400	
Sound pressure level at 1.4 m (1)	Max~Min	dB(A) 35~22		41~28	
Sound power level (1)	Max~Min	dB(A) 51~38		56~43	
External dimensions	LxHxD	mm 630x260x570			
Net weight	Kg	18		19.2	
Refrigerant connections	Liquid/Gas	Ø mm (inch) 6.35 (1/4") - 12.7 (1/2")			
Condensate drain	Ø mm	32			
Accessories					
Decorative panel		TFP 155 XRV-P			
Dimensions	LxHxD	mm 647x50x647			
Net weight	Kg	2.5			
Remote control		DHIR-5-6-XRV-K-P			
Wired remote control		DHW-5-6-XRV-K-P			
Optional parts					
Centralized control		see page 117			

(1) Values related to Max and Min speed of 7 levels settable by remote control.

HTBU XRV-P Cassette 84x84



The control must be purchased as an accessory



Optimised fan design to attenuate air resistance and reduce noise level

Condensate drain pump with possibility of raising the discharge up to 750 mm from the lower height

Pre-set for the connection of an outside air intake channel

Model		HTBU 565 XRV-P	HTBU 715 XRV-P	HTBU 905 XRV-P	HTBU 1125 XRV-P	HTBU 1405 XRV-P
Control (included)	type	none				
Rated cooling capacity	kW	5.60	7.10	9.00	11.20	14.00
Rated heating capacity	kW	6.30	8.00	10.00	12.50	16.00
Electrical data						
Power supply	Ph-V-Hz	1-220~240V-50Hz				
Electrical absorption	W	31	46	75	94	
Product specifications						
Air flow (1)	Max~Min	m³/h 1029~704		1596~1034		1727~1224
Sound pressure level at 1.4 m (1)	Max~Min	dB(A) 43~34		45~34		50~38
Sound power level (1)	Max~Min	dB(A) 56~47		58~47		64~52
External dimensions	LxHxD	mm 840x230x840			840x300x840	
Net weight	Kg	23.2		28.4		30.7
Refrigerant connections	Liquid/Gas	Ø mm (inch) 9.52 (3/8") - 15.9 (5/8")				
Condensate drain	Ø mm	32				
Accessories						
Decorative panel		TBP 712 IHXR				
Dimensions	LxHxD	mm 950x70x950				
Net weight	Kg	5.8				
Remote control		DHIR-5-6-XRV-K-P				
Wired remote control		DHW-5-6-XRV-K-P				
Optional parts						
Centralized control		see page 117				

(1) Values related to Max and Min speed of 7 levels settable by remote control.