

PROJECT VRF R410A FULL DC INVERTER

.....

HKEU XRV-P Wall



The control must be purchased as an accessory



New design

203 mm deep (2.20 kW) | Extremely compact design

29 dB(A) (2.20~2.80 kW) | Extremely quiet
Standard washable filter

Model		HKEU 225 XRV-P	HKEU 285 XRV-P	HKEU 365 XRV-P	HKEU 455 XRV-P	HKEU 565 XRV-P	HKEU 715 XRV-P	HKEU 905 XRV-P	
Control (included)	type				none				
Rated cooling capacity	kW	2.20	2.80	3.60	4.50	5.60	7.10	9.00	
Rated heating capacity	kW	2.40	3.20	4.00	5.00	6.30	8.00	10.00	
Electrical data									
Power supply	Ph-V-Hz	1-220~240V-50Hz							
Electrical absorption	W	28		30	40	45	55	82	
Product specifications									
Air flow (1)	Max~Min	m ³ /h	422~356	417~316	656~488	594~424	747~547	1195~809	1421~867
Sound pressure level at 1 m (1)	Max~Min	dB(A)	31~29	31~29	33~30	35~31	38~34	44~36	48~38
Sound power level (1)	Max~Min	dB(A)	46~44	46~44	48~45	50~46	53~49	59~51	63~53
Dimensions	LxHxD	mm	835x280x203			990x315x223		1194x343x262	
Net weight		Kg	8.4	9.5	11.4	12.8		17	
Refrigerant connections	Liquid/Gas	Ø mm (inch)	6.35 (1/4") - 12.7 (1/2")					9.52 (3/8") - 15.9 (5/8")	
Condensate drain		Ø mm	16						
Accessories									
Remote control					DHIR-5-6-XRV-K-P				
Wired remote control					DHW-5-6-XRV-K-P				
Optional parts									
Centralized control					see page 117				

(1) Values related to Max and Min speed of 7 levels settable by remote control.

HSFU XRV-P Floor/ceiling



The control must be purchased as an accessory



Auto Swing function | Optimises the distribution of air flow in the room

Built-in electronic expansion valve

Easy installation with unit mounted to the floor or to the ceiling

Model		HSFU 565 XRV-P	HSFU 715 XRV-P	HSFU 905 XRV-P	HSFU 1125 XRV-P	HSFU 1405 XRV-P	
Control (included)	type						
Rated cooling capacity	kW	5.60	7.10	9.00	11.20	14.00	
Rated heating capacity	kW	6.30	8.00	10.00	12.50	15.00	
Electrical data							
Power supply	Ph-V-Hz	1-220~240V-50Hz					
Electrical absorption	W	115	115	130	180	180	
Product specifications							
Air flow (1)	Max~Min	m ³ /h	930~720		1280~1050		1890~1580
Sound pressure level at 1 m (1)	Max~Min	dB(A)	43~38		45~40		47~42
Sound power level (1)	Max~Min	dB(A)	56~51		58~53		60~55
Dimensions	LxHxD	mm	990x660x203		1280x660x203		1670x680x244
Net weight		Kg	28		35		48
Refrigerant connections	Liquid/Gas	Ø mm (inch)	9.52 (3/8") - 15.9 (5/8")				
Condensate drain		Ø mm	16				
Accessories							
Remote control					DHIR-5-6-XRV-K-P		
Wired remote control					DHW-5-6-XRV-K-P		
Optional parts							
Centralized control					see page 117		

(1) Values related to Max and Min speed of 7 levels settable by remote control.