

# KAITEKI

MONOSPLIT R32



Standard remote control  
with built-in temperature sensor  
(I-Feel function)



HKETM 260-710 ZAL



HCNTS 260-350 ZA



HCNTS 530 ZA




HCNTS 710 ZA

Indoor unit model			HKETM 260 ZAL	HKETM 350 ZAL	HKETM 530 ZAL	HKETM 710 ZAL
Outdoor unit model			HCNTS 260 ZA	HCNTS 350 ZA	HCNTS 530 ZA	HCNTS 710 ZA
Rated capacity (T=+35°C)	Cooling	kW	2.60 (0.94~3.35)	3.40 (1.00~3.77)	5.10 (1.25~5.90)	6.81 (1.83~7.80)
		kW	0.79 (0.24~1.38)	1.13 (0.29~1.50)	1.58 (0.33~2.35)	2.26 (0.41~2.82)
		EER <sup>3</sup>	3.30	3.01	3.23	3.02
		626/2011 <sup>1</sup> / SEER <sup>2</sup>	A++ / 6.3	A++ / 6.1	A++ / 6.1	A++ / 6.1
Rated capacity (T=+7°C)	Heating	kW	2.75 (0.94~3.38)	3.42 (1.00~3.81)	5.13 (1.25~6.08)	6.87 (1.85~7.90)
		kW	0.73 (0.24~1.55)	0.92 (0.29~1.72)	1.38 (0.34~2.54)	2.06 (0.42~3.01)
		COP <sup>3</sup>	3.75	3.71	3.71	3.33
		626/2011 <sup>1</sup> / SCOP <sup>2</sup>	A+ / 4.0	A+ / 4.0	A+ / 4.0	A+ / 4.0
Operating limits (outside temperature) Cooling / Heating		°C	-15~53 / -20~30			
GWP <sup>4</sup> / Kg refrigerant pre-load / tCO <sub>2</sub> EQ.			675 / 0.55 / 0.371	675 / 0.55 / 0.371	675 / 0.92 / 0.621	675 / 1.14 / 0.770
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø12.74(1/2")
Max splitting length		m	25	25	25	25
Max height difference !.U./O.U.		m	10	10	10	10
Split length without additional charge		m	5	5	5	5
Additional load		g/m	15	15	25	25
<b>Indoor units specifications</b>						
Dimensions / Net weight		mm (LxDxH) / kg	777x201x250 / 8	777x201x250 / 8	910x206x294 / 10	1010x220x315 / 13
Sound pressure level (I.U.)		SHi/Hi/Mi/Lo/U/Lo dB(A)	40/37/33/25/22	40/37/33/25/22	43/41/38/35/27	44/41/38/34/30
Sound power level (I.U.)		Hi dB(A)	50	50	53	54
<b>Outdoor units specifications</b>						
Dimensions		mm (LxDxH)	777x290x498	777x290x498	853x349x602	920x380x699
Net weight		Kg	24	24	35	40
Sound pressure level (O.U.) / Sound power level (O.U.)		dB(A)	50 / 60	50 / 60	55 / 65	57 / 67

1. 2. 3. 4. Please refer to the Hokkaido general catalogue for regulations.

# HOKKAIDO



09-2021:

**HOKKAIDO srl** Ph. +39 051 4133 111  
Via della Salute 14 Fax +39 051 4133 146  
40132 Bologna Italy **www.hokkaido.it**