

INDOOR UNITS

2 CAPACITIES
3.50~5.00 kW

COMPACT DESIGN
178mm height for recessed installation in false ceilings



TOP
1000
Drain pump with the highest discharge head (maximum lift) compared with all competitors in its market segment.

MEMORY FUNCTION
WASHABLE FILTER
CONDENSATE DRAIN PUMP INCLUDED max height difference **1000 mm**
REMOTE CONTROL INCLUDED

Wired remote control with optional integrated WiFi

1-WAY CASSETTE

Model			MTSGM 351 ZL	MTSGM 531 ZL
Type			Cassette type indoor unit	
Control			Remote control	
Nominal capacity	Cooling	kW	3.50	5.00
	Heating	kW	3.80	5.60
Electrical data				
Power supply		Ph-V-Hz	-	-
Connection wires between I.U. and O.U.		no.	4	4
Refrigerant circuit data				
Liquid/gas refrigerant pipe diameter		mm (inches)	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø12.74(1/2")
Product specifications				
Dimensions	LxDxH	mm	987x385x178	987x385x178
	Net weight	Kg	19	20
Sound power level	Hi~Lo	dB(A)	53/50/43/41	56/53/48/45
Sound pressure level	Hi~Lo	dB(A)	42/39/35/31	43/40/35/32
Volume of air treated	Hi~Lo	m ³ /h	600/500/440/390	700/600/500/450
Accessories			MTSPG 351 Z	
Decorative panel				
Optional parts				
Individual wired control with connection cable			M-RF-CW2-L-G + CW2-SE-TF-ADAPTOR	
Wired control for centralized control			M-RF-CW3-L-G	
Wired control with integrated Wi-Fi module			DMW-ZAL-LCAC WiFi	
Centralized control (only possible with wired control)			M-V-CC-1255-G2	

3 CAPACITIES
2.60~5.00 kW

MAXIMUM COMPACTNESS
only **200 mm** high

MEMORY FUNCTION



TOP
60 Pa
Discharge head value higher than the average for competitors in this market segment.

WASHABLE FILTER
6 FAN SPEED LEVELS
DAILY TIMER
WIRED CONTROL INCLUDED

Wired remote control with optional integrated WiFi

DUCTED

Model			MUCGM 261 ZL	MUCGM 351 ZL	MUCGM 531 ZL
Type			Ducted type indoor unit		
Standard control			Wired control		
Nominal capacity	Cooling	kW	2.60	3.50	5.00
	Heating	kW	2.80	3.80	5.60
Electrical data					
Power supply		Ph-V-Hz	-	-	-
Connection wires between I.U. and O.U.		no.	4	4	4
Refrigerant circuit data					
Liquid/gas refrigerant pipe diameter		mm (inches)	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø12.74(1/2")
Product specifications					
Dimensions	LxDxH	mm	710x450x200	710x450x200	1010x450x200
	Net weight	Kg	18.5	19	25
Sound power level	Hi~Lo	dB(A)	57/55/54/53/52/51/50	55/53/52/51/50/49/48	57/55/55/54/54/53/50
Sound pressure level	Hi~Lo	dB(A)	41/39/38/37/36/35/34	39/37/36/35/34/33/32	41/39/39/38/38/37/34
Volume of air treated	Hi~Lo	m ³ /h	700/670/640/610/580/550/520	650/560/520/480/450/410/380	880/840/810/790/770/750/730
Fan's static pressure	Std/Max	Pa	25/60	25/60	25/60
Optional parts					
Wi-Fi module			Integrated in the standard wired control		
Centralized control			M-V-CC-1255-G2		