

INDOOR UNITS

3 CAPACITIES

2.60~5.00 kW

7 FAN SPEED levels

ELEGANT & COMPACT DESIGN

215 mm deep



MEMORY FUNCTION,
I-FEEL FUNCTION, X-FAN FUNCTION

DOUBLE AIR DELIVERY

8° C HEATING

REMOTE CONTROL INCLUDED



Wi-Fi INTEGRATED

CONSOLE

Model			MFIGM 261 ZAL	MFIGM 351 ZAL	MFIGM 531 ZAL
Type			Console type indoor unit		
Control			Remote control		
Nominal capacity	Cooling	kW	2.60	3.50	5.00
	Heating	kW	2.80	3.80	5.60
Electrical data					
Power supply		Ph-V-Hz	-	-	-
Connection wires between I.U. and O.U.		no.	4	4	4
Refrigerant circuit data					
Liquid/gas refrigerant pipe diameter		mm (inches)	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø12.74(1/2")
Product specifications					
Dimensions	LxDxH	mm	700x215x600	700x215x600	700x215x600
	Net weight	Kg	15.5	16	16
Sound power level	Hi~Lo	dB(A)	52/48/46/44/41/38/35	55/51/49/47/44/40/36	60/58/56/53/51/48/43
Sound pressure level	Hi~Lo	dB(A)	39/36/34/32/29/26/23	44/40/38/36/33/29/25	49/47/45/42/40/37/32
Volume of air treated	Hi~Lo	m³/h	500/430/410/370/330/280/250	600/520/480/440/400/360/280	750/670/600/520/470/430/350
Optional parts					
Individual wired control			M-RF-CW2-L-G / M-RF-CW3-L-G		
Wi-Fi module			Included		

2 CAPACITIES

3.50~5.00 kW

COMPACT DESIGN

265 mm height for recessed installation in false ceilings

MEMORY FUNCTION



TOP

1000

Built-in condensate drain pump, with the highest discharge head (maximum lift) compared with all competitors in its market segment.

WASHABLE FILTER

X-FAN

TOTAL TEMPERATURE CONTROL

REMOTE CONTROL INCLUDED



Wired remote control with optional integrated Wi-Fi

COMPACT CASSETTE

Model			MTFGM 351 ZL	MTFGM 531 ZL
Type			Cassette type indoor unit	
Control			Remote control	
Nominal capacity	Cooling	kW	3.50	5.00
	Heating	kW	3.80	5.60
Electrical data				
Power supply		Ph-V-Hz	-	-
Connection wires between I.U. and O.U.		no.	4	4
Refrigerant circuit data				
Liquid/gas refrigerant pipe diameter		mm (inches)	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø12.74(1/2")
Product specifications				
Dimensions	LxDxH	mm	570x570x265	570x570x265
	Net weight	Kg	17	17
Sound power level	Hi~Lo	dB(A)	57/55/52/50/48/46/44	59/55/52/50/48/46/44
Sound pressure level	Hi~Lo	dB(A)	41/39/36/34/32/30/28	43/39/36/34/32/30/28
Volume of air treated	Hi~Lo	m ³ /h	560/540/490/450/420/380/350	650/540/490/450/420/380/350
Accessories				
Decorative panel			MTFPG 350 ZA	
Optional parts				
Individual wired control with connection cable			M-RF-CW2-L-G + CW2-SE-TF-ADAPTOR	
Wired control for centralized control			M-RF-CW3-L-G	
Wired control with integrated Wi-Fi module			DMW-ZAL-LCAC Wi-Fi	
Centralized control (only possible with wired control)			M-V-CC-T255-G2	