

INDOOR UNITS

4 CAPACITIES
2.60~7.20 kW

7 SPEED LEVELS
of ventilation



- I-FEEL FUNCTION
- SELF-CLEAN FUNCTION
- COLD PLASMA FILTER
- REMOTE CONTROL INCLUDED

WALL ACTION



Model			MKEGM 267 ZAL	MKEGM 357 ZAL	MKEGM 537 ZAL	MKEGM 717 ZAL
Type	Wall type indoor unit					
Control	Remote control					
Nominal capacity	Cooling	kW	2.60	3.50	5.00	7.20
	Heating	kW	2.80	3.80	5.60	8.50
Electrical data						
Power supply		Ph-V-Hz	-	-	-	-
Connection wires between I.U. and O.U.		no.	4	4	4	4
Refrigerant circuit data						
Liquid/gas refrigerant pipe diameter		mm (inches)	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø12.74(1/2")
Product specifications						
Dimensions	LxDxH	mm	708x185x260	835x200x275	943x246x333	943x246x333
	Net weight	Kg	7	9	13	13.5
Sound power level	Hi~Lo	dB(A)	55/48/46/44/40/37/33	59/50/47/45/41/38/35	60/58/56/54/48/44/41	65/56/54/52/50/46/42
Sound pressure level	Hi~Lo	dB(A)	38/36/34/32/28/25/21	42/38/35/33/29/26/23	47/45/43/41/35/30/28	50/46/44/42/40/36/32
Volume of air treated	Hi~Lo	m ³ /h	500/470/430/390/320/270/250	650/550/470/420/380/350/310	1000/960/870/810/720/640/600	1050/900/740/690/640/590/540
Optional parts						
Individual wired control	M-RF-CW2-L-G / M-RF-CW3-L-G					
Wi-Fi module	Integrated					

4 CAPACITIES
2.60~7.20 kW

ELEGANT & COMPACT DESIGN
210 mm depth for the 2.60 and 3.50 kW models



MAXIMUM SILENCE
only 22 dB(A) in Low mode for the 2.60 kW model

- I-FEEL FUNCTION
- COLD PLASMA FILTER
- REMOTE CONTROL INCLUDED

WALL AIRPRO PLUS



Model			MKEGM 265 ZAL	MKEGM 355 ZAL	MKEGM 535 ZAL	MKEGM 715 ZAL
Type	Wall type indoor unit					
Control	Remote control					
Nominal capacity	Cooling	kW	2.60	3.50	5.00	7.20
	Heating	kW	2.80	3.80	5.60	8.50
Electrical data						
Power supply		Ph-V-Hz	-	-	-	-
Connection wires between I.U. and O.U.		no.	4	4	4	4
Refrigerant circuit data						
Liquid/gas refrigerant pipe diameter		mm (inches)	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø9.52(3/8")	ø6.35(1/4") / ø12.74(1/2")	ø6.35(1/4") / ø15.9(5/8")
Product specifications						
Dimensions	LxDxH	mm	865x290x210	865x290x210	996x301x225	1101x327x249
	Net weight	Kg	10.5	10.5	13	16
Sound power level	Hi~Lo	dB(A)	58/52/50/48/44/40/36	58/53/51/49/46/43/37	60/57/55/54/52/50/46	64/59/56/55/53/51/48
Sound pressure level	Hi~Lo	dB(A)	41/38/36/34/30/26/22	43/39/37/35/32/29/23	43/41/39/37/35/32/31	48/44/41/40/38/36/33
Volume of air treated	Hi~Lo	m ³ /h	660/590/540/490/450/420/390	680/590/540/490/450/420/390	850/750/680/610/570/520/460	1250/1100/1000/950/900/850/800
Optional parts						
Individual wired control	M-RF-CW2-L-G / M-RF-CW3-L-G					
Wi-Fi module	Integrated					